

Adult Phenolic Folding Shower Seats

Rectangle

Configuration:
62 Series
Phenolic

Application Use:



Specifications

Folding shower seat manufactured by ELCOMA from 1" (25mm) diameter, 18 gauge and 1.25" x 1.25" (32mm x 32mm), 16 gauge, type 304 stainless steel tubing with #4 satin finish. Wall mount brackets shall be 12 gauge type 304 stainless steel. Solid Phenolic seat shall be 1/2" (13mm) thick and shall be fire and mildew resistant. Shower Seat shall comply with all applicable federal, provincial and local building and safety codes.

White shown, Also available in Woodgrain



Custom sizes are available to suit special requirements.

24" x 16" (609mm x 406mm)	White	Model # 62-PH2401
24" x 16" (609mm x 406mm)	Woodgrain	Model # 62-PH2415
26" x 16" (660mm x 406mm)	White	Model # 62-PH2601
26" x 16" (660mm x 406mm)	Woodgrain	Model # 62-PH2615
28" x 16" (711mm x 406mm)	White	Model # 62-PH2801
28" x 16" (711mm x 406mm)	Woodgrain	Model # 62-PH2815
30" x 16" (762mm x 406mm)	White	Model # 62-PH3001
30" x 16" (762mm x 406mm)	Woodgrain	Model # 62-PH3015
32" x 16" (812mm x 406mm)	White	Model # 62-PH3201
32" x 16" (812mm x 406mm)	Woodgrain	Model # 62-PH3215
34.5" x 16" (876mm x 406mm)	White	Model # 62-PH34501
34.5" x 16" (876mm x 406mm)	Woodgrain	Model # 62-PH34515

Elcoma Shower Seats have been designed and tested to withstand 400lbs. (182kgs) of load when properly installed.* This exceeds HUD, FHA, VA, ADA, ANSI and other federal, provincial, and local codes. *Shower seats can only be as strong as what they are mounted to. It is imperative when installing any shower seat to consult with a qualified contractor to insure you have sufficient backing.

